



Manufacturer		Type testing No.	EAPR-GS-7670/12
		Location	Schruns
Model	Geronimo S	Bad Grönenbach:	29.11.12



EAPR GmbH - Marktstr. 11 - D-87730 Bad Grönenbach - Germany

Date of testing	Minimum take off weight		Maximum take off weight	
	18.11.12		14.11.12	
Testpilot	Josef Bauer		Mike Küng	
Harness	EAPR-Testequipment		EAPR Testequipment	
Pilot's take off weight	60 kg		90 kg	

Classification	B
----------------	---



Test-criteria	41231	Evaluation	41227	Evaluation
1. Inflation / take-off - 4.1.1				
Rising behavior	Smooth, easy and constant rising	A	Smooth, easy and constant rising	A
Special take off technique required	No	A	No	A
2. Landing - 4.1.2				
Special landing technique required	No	A	No	A
3. Speeds in straight flight - 4.1.3				
Trim speed more than 30km/h	Yes	A	Yes	A
Speed range using the controls larger than 10km/h	Yes	A	Yes	A
Minimum speed	Less than 25 km/h	A	Less than 25 km/h	A
4. Control movement - 4.1.4				
Max. weight in flight up to 80kg		-		-
Max. weight in flight 80 to 100kg	Increasing > 60cm	A	Increasing > 60cm	A
Max. weight in flight greater than 100kg		-		-
5. Pitch stability exiting accelerated flight - 4.1.5				
Dive forward angle on exit	Dive forward less than 30°	A	Dive forward less than 30°	A
Collapse occurs	No	A	No	A
6. Pitch stability operating controls during accelerated flight - 4.1.6				
Collapse occurs	No	A	No	A
7. Roll stability and damping - 4.1.7				
Oscillations	Reducing	A	Reducing	A
8. Stability in gentle spirals - 4.1.8				
Tendency to return to straight flight	Spontaneous exit	A	Spontaneous exit	A
9. Behaviour in a steeply banked turn - 4.1.9				
Sink rate after two turns	More than 14m/s	B	12m/s to 14m/s	A
10. Symmetric front collapse - 4.1.10				
Entry	Rocking back less than 45°	A	Rocking back less than 45°	A
Recovery	Spontaneous in less than 3 sec	A	Spontaneous in less than 3 sec	A
Dive forward angle on exit	0° - 30° Keeping course	A	0° - 30° Keeping course	A
Cascade occurs	No	A	No	A
Entry	Rocking back less than 45°	A	Rocking back less than 45°	A
Recovery	Spontaneous in less than 3 sec	A	Spontaneous in 3 to 5 sec	B
Dive forward angle on exit	0° - 30° Keeping course	A	30° - 60° Entering a turn of less than 90°	B
Cascade occurs	No	A	No	A
11. Exiting deep stall (parachutal stall) - 4.1.11				

Deep stall achieved		No		Yes										
Recovery				NA		Spontaneous in less than 3 sec		A						
Dive forward angle on exit				NA		0° - 30°		A						
Change of course				NA		Changing course less than 45°		A						
Cascade occurs				NA		No		A						
12. High angle of attack recovery - 4.1.12														
Recovery		Spontaneous in less than 3 sec		A		Spontaneous in less than 3 sec		A						
Cascade occurs		No		A		No		A						
13. Recovery from a developed full stall - 4.1.13														
Dive forward angle on exit		30° - 60°		B		30° - 60°		B						
Collapse		No collapse		A		No collapse		A						
Cascade occurs (other than collapse)		No		A		No		A						
Rocking backward		Less than 45°		A		Less than 45°		A						
Line tension		Most lines tight		A		Most lines tight		A						
14. Asymmetric collapse (trim speed) - 4.1.14														
Change of course until re-inflation		trim speed, max 50% collapse	< 90°	Dive or roll angle	15° - 45°	A		< 90°	Dive or roll angle	0° - 15°	A			
Re-inflation behavior			Spontaneous re-inflation				A		Spontaneous re-inflation				A	
Total change of course			Less than 360°				A		Less than 360°				A	
Collapse on the opposite side occurs			No				A		No				A	
Twist occurs			No				A		No				A	
Cascade occurs			No				A		No				A	
Change of course until re-inflation		trim speed, max 75% collapse	90° - 180°	Dive or roll angle	15° - 45°	B		90° - 180°	Dive or roll angle	15° - 45°	B			
Re-inflation behavior			Spontaneous re-inflation				A		Spontaneous re-inflation				A	
Total change of course			Less than 360°				A		Less than 360°				A	
Collapse on the opposite side occurs			No				A		No				A	
Twist occurs			No				A		No				A	
Cascade occurs			No				A		No				A	
Change of course until re-inflation		accelerated, max 50% collapse	< 90°	Dive or roll angle	15° - 45°	A		< 90°	Dive or roll angle	15° - 45°	A			
Re-inflation behavior			Spontaneous re-inflation				A		Spontaneous re-inflation				A	
Total change of course			Less than 360°				A		Less than 360°				A	
Collapse on the opposite side occurs			No				A		No				A	
Twist occurs			No				A		No				A	
Cascade occurs			No				A		No				A	
Change of course until re-inflation		accelerated, max 75% collapse	90° - 180°	Dive or roll angle	15° - 45°	B		90° - 180°	Dive or roll angle	15° - 45°	B			
Re-inflation behavior			Spontaneous re-inflation				A		Spontaneous re-inflation				A	
Total change of course			Less than 360°				A		Less than 360°				A	
Collapse on the opposite side occurs			No				A		No				A	
Twist occurs			No				A		No				A	
Cascade occurs			No				A		No				A	
15. Directional control with a maintained asymmetric collapse - 4.1.15														
Able to keep course straight		Yes		A		Yes		A						
180° turn away from the collapsed side possible in 10 sec		Yes		A		Yes		A						
Amount of control range between turn and stall or spin		More than 50% of the symmetric control travel		A		More than 50% of the symmetric control travel		A						
16. Trim speed spin tendency - 4.1.16														
Spin occurs		No		A		No		A						
17. Low speed spin tendency - 4.1.17														
Spin occurs		No		A		No		A						
18. Recovery from a developed spin - 4.1.18														
Spin rotation angle after release		Stops spinning in less than 90°		A		Stops spinning in less than 90°		A						
Cascade occurs		No		A		No		A						
19. B-line-stall - 4.1.19														
Change of course before release		Changing course less than 45°		A		Changing course less than 45°		A						
Behaviour before release		Remains stable with straight span		A		Remains stable with straight span		A						
Recovery		Spontaneous in less than 3 sec		A		Spontaneous in less than 3 sec		A						
Dive forward angle on exit		0° - 30°		A		30° - 60°		A						
Cascade occurs		No		A		No		A						
20. Big ears - 4.1.20														
Entry procedure		Standard technique		A		Special device required		A						
Behaviour during big ears		Stable flight		A		Stable flight		A						
Recovery		Recovery through pilot action in less than a further 3 sec		B		Spontaneous in less than 3 sec		A						
Dive forward angle on exit		0° - 30°		A		0° bis 30°		A						
21. Big Ears in accelerated flight - 4.1.21														
Entry procedure		Standard technique		A		Special device required		A						
Behaviour during big ears		Stable flight		A		Stable flight		A						
Recovery		Recovery through pilot action in less than a further 3 sec		B		Spontaneous in 3 to 5 sec		A						
Dive forward angle on exit		0° - 30°		A		0° bis 30°		A						
Behaviour immediately after releasing the accelerator while maintaining big ears		Stable flight		A		Stable flight		A						
22. Behaviour exiting a steep spiral - 4.1.22														

Tendency to return to straight flight	Spontaneous exit	A	Spontaneous exit	A
Turn angle to recover normal flight	Less than 720°, spontaneous recovery	A	Less than 720°, spontaneous recovery	A
23. Alternative means of directional control - 4.1.23				
180° turn achievable in 20 sec	Yes	A	Yes	A
Stall or spin occurs	No	A	No	A
24. Any other flight procedure and/or configuration described in the user's manual - 4.1.24				
Procedure works as described		NA		NA
Procedure suitable for novice pilots		NA		NA
Cascade occurs		NA		NA
25. Remarks of testpilot:				
Copyright Ralf Antz 2010		This Flight Test Report was generated automatically and is valid without signature		